

Deskstar™ 7K3000

3.5-INCH HARD DISK DRIVES

HITACHI
Inspire the Next

Enormous capacity and exceptional performance for desktop computing

Highlights

- > Up to 3TB¹ for the highest capacity needs
- > 7200 RPM performance
- > 6Gb/s SATA interface for improved performance over previous generation product
- > Eco-friendly, Halogen-free design
- > Designed to leverage new platforms and modern operating systems

Applications

- > Consumer and commercial computers
- > External storage
- > PC gaming
- > Video editing arrays



3TB, 2TB and 1.5TB | 7200 RPM
SATA 6Gb/s



Features and Benefits

	Feature / Function	Benefits
Capacity	3TB 2TB & 1.5TB models available	Highest capacity available in a single hard drive
	Performance	64MB cache buffer SATA 6Gb/s interface
Reliability	Thermal Fly-height Control (TFC)	Better soft error rate for improved reliability and performance
	Head load/unload	Protects disk during non-operation
	LDPC and CRC protection	Data integrity enhanced throughout circuits
	SMART command transport	Adaptive error correction
	Internal thermal sensor	Improves data integrity
Power	Advanced Power Management HiVERT™ technology	Reduces power during idle periods Best-of-breed power consumption

Big storage paves the way for new platforms

The Deskstar™ 7K3000 is Hitachi's first hard drive to deliver an enormous three terabytes of storage capacity and 7200 RPM performance in a standard 3.5-inch form factor. The 7K3000 is also the first Hitachi hard drive with a 6Gb/s SATA interface, which along with its 64MB cache buffer delivers a big boost to performance over the previous generation product. The Deskstar 7K3000 is designed to allow manufacturers to leverage the benefits of the latest components and operating systems to deliver high-performance, high-capacity, power-efficient systems. Manufacturers planning to use the highest capacity 3TB drive in systems should consult the Hitachi High Capacity Technology Brief. Deskstar 7K3000 is also available in 2TB and 1.5TB models that accommodate existing systems, as well as new designs.

Excellent performance and energy efficiency

The Deskstar 7K3000 delivers an extraordinary blend of capacity, performance and power efficiency. All capacities will ship with 64MB cache buffer and 6Gb/s SATA interface. This configuration shows an improvement of up to 27% over previous generation products in PCMark Vantage testing scores. In addition, the 2TB 7K3000 offers idle power savings of up to 30% over previous generation products, making it an ideal storage platform for desktop computing. Leveraging eighth-generation power management technology, including power-saving innovations like HiVERT™ technology, this drive delivers excellent power efficiency and thermal emissions to help manufacturers meet energy compliance targets and extend drive life.

Eco-friendly storage

The Deskstar 7K3000 demonstrates Hitachi ecological leadership with its halogen-free design and power-efficient operation. Both these features helped qualify the drive for the Hitachi EcoTrac classification, which identifies products that minimize environmental impact in the areas of product design, manufacturing, operation and disposal.

Specifications

Model(s)	HDS723030ALA640 HDS723020BLA642 HDS723015BLA642	
Configuration		
Interface	SATA 6Gb/s	
Capacity (TB) ¹	3 / 2 / 1.5	
Sector size (bytes)	512	
Max. areal density (Gbits/sq. in.)	411	
Performance		
Data buffer (MB) ²	64	
Rotational speed (RPM)	7200	
Media transfer rate (Mbits/s, max)	1656	
Interface transfer rate (MB/s, max)	600	
Reliability		
Error rate (non-recoverable, bits read)	1 in 10 ¹⁴	
Load/unload cycles (at 40°C)	3TB <3TB	600,000 300,000
Availability ³ (hrs/day x days/wk)	24x7	
Acoustics		
Idle (Bels, typical)	3TB <3TB	2.9 2.7
Power		
Requirement	3TB <3TB	+5 VDC (+/-5%) +12 VDC (+10%/-8%) +5 VDC (+/-5%) +12 VDC (+/-10%)
Startup current (A, max.)	1.2 (+5V), 2.0 (+12V)	
Idle (W)	3TB <3TB	6.8 5.2
Physical size		
z-height (mm)	26.1	
Dimensions (width x depth, mm)	101.6 (+/-0.25) x 147	
Weight (typical, g, max.)	3TB <3TB	690 680
Environmental (operating)		
Ambient temperature	3TB <3TB	5° to 60° C 0° to 60° C
Relative humidity (non-condensing)	8% to 90%	
Shock (half-sine wave, G (2ms))	70	
Vibration, random (G RMS 5 to 500 Hz)	0.67 (XYZ)	
Environmental (non-operating)		
Ambient temperature	-40° to 70° C	
Relative humidity (non-condensing)	5% to 95%	
Shock (half-sine wave, G)	3TB <3TB	300 (1ms) 300 (2ms)
Vibration, random (G RMS 2 to 200 Hz)	1.04 (XYZ)	

¹ One GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the hard drive, the computer's operating system, and other factors.

² Portion of buffer capacity used for drive firmware

³ Intended for low duty cycle, non mission-critical applications in PC, gaming and external storage environments, which may vary from application to application. Note that customer environments may vary from application to application.

Hitachi Global Storage Technologies trademarks are intended and authorized for use only in countries and jurisdictions in which Hitachi Global Storage Technologies has obtained the rights to use, market and advertise the brand. Contact Hitachi Global Storage Technologies for additional information. Hitachi Global Storage Technologies shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. Hitachi Global Storage Technologies shall not be liable to third parties for unauthorized use of Hitachi Global Storage Technologies trademarks.

References in this publication to Hitachi Global Storage Technologies' products, programs or services do not imply that Hitachi Global Storage Technologies intends to make these available in all countries in which it operates.

Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary. Please visit the Support section of our website, www.hitachigst.com/support, for additional information on product specifications. Photographs may show design models.

Hitachi quality and service

All Hitachi hard drives are designed to the highest quality standards with field-proven components. They are backed by Hitachi's worldwide technical support and integration services, enabling customers around the globe to bring their products to market quickly.

How to read the Deskstar model number

HDS723030ALA640 = 3TB, 64MB buffer

H = Hitachi

D = Deskstar

S = Series prefix

72 = 7200 RPM

30 = Full capacity—3TB

30 = Capacity this model, 30 = 3TB

(20 = 2TB, 15 = 1.5TB)

A = Generation code

L = 26.1mm z-height

A6 = Interface, SATA 6Gb/s

4 = 64MB buffer

0 = Reserved (2 = Reserved)

Information and Technical Support

www.hitachigst.com (Main Web site)

www.hitachigst.com/partners (Partner Web site)

North America

support_usa@hitachigst.com

Toll free: 1 888 426-5214, Direct: 1 507 322-2370

Asia Pacific

support_ap@hitachigst.com / 65 6840 9595

EMEA and UK

support_uk@hitachigst.com / 44 20 7133 0032

Germany

support_uk@hitachigst.com / 49 6929 993601

Program Support

Partners First™ Program

channelpartners@hitachigst.com

© 2010 Hitachi Global Storage Technologies

Hitachi Global Storage Technologies
3403 Yerba Buena Road
San Jose, CA 95135 USA

Produced in the United States 10/10. All rights reserved.

Deskstar™ and HiVERT™ are trademarks of Hitachi Global Storage Technologies. Hitachi and Hitachi Inspire the Next logo are trademarks of Hitachi, Ltd in the U.S., Japan and/or other countries. Other trademarks are the property of their respective companies.

The EcoTrac symbol identifies Hitachi hard drives that deliver on the principles of lower operating costs, safer product disposal and a more sustainable environment.