

CinemaStar™ C5K250

2.5-INCH CE HARD DISK DRIVES

HITACHI
Inspire the Next

Consumer Electronics storage for digital video applications

Highlights

- > Low-profile 2.5" design - 9.5mm
- > CE hard drive with capacities up to 250GB
- > SmoothStream™ technology
- > Silent-seek acoustics for CE applications
- > SMART Command Transport (SCT) for streaming optimization
- > Best-in-class power utilization and heat emission

Applications

- > Digital Video Recorders / Set-top Boxes
- > Portable Video Players
- > DVR-enabled Televisions
- > DVD/HDD Recorders
- > High-end Audio Systems



250, 160, 120 and 80 GB | 5400 RPM
SATA 1.5 Gb/s

Features and Benefits

| | Feature / Function | Benefits |
|--------------------|--|--|
| Capacity | Up to 250 GB of storage | * Capacity equivalence of 250 hours standard video, 89 movies, 62,500 4-min songs or 125 video games |
| Reliability | TMR -IrMnCr read head | Better performance & data reliability |
| | Thermal Fly-height Control (TFC) | Better soft error rate for improved reliability |
| | Media Maintenance | Prevents track wear-out |
| Performance | SMART Command Transport (SCT) ERP Control | Fewer streaming disruptions and improved error recovery timing for optimum A/V performance |
| Acoustics | Silent-seek | Ultra quiet operation |
| Interface | SATA | SmoothStream Technology |

*Actual storage may vary depending on the compression rate applied. Capacities represented may not be combined.

Expanding the CinemaStar family

CinemaStar C5K250, Hitachi's new 2.5-inch consumer electronics hard drive, uses Perpendicular Magnetic Recording (PMR) technology to deliver capacities up to 250 GB. This drive, based on proven, industry-leading technology, has been customized to support digital video applications. Hitachi SmoothStream technology is enabled to support the ATA-7 streaming command set, and SCT provides time-limited error recovery and thermal monitoring capabilities. CinemaStar C5K250 has been enhanced with silent-seek acoustics to improve the already bedroom-quiet operation. Low power consumption and cool-running operation make the C5K250 an ideal choice for DVR applications. This second generation compact CinemaStar drive expands the Hitachi product lineup to provide manufacturers with energy-efficient options for next-generation slim DVR designs.

Reliability leadership

Hitachi has enhanced TFC for improved error rates and tunnel magneto-resistive (TMR) read heads for enhanced data reliability on the CinemaStar C5K250. Hitachi Design Studios offer customers CE system design and integration services including, but not limited to hard drive selection, optimization, software compatibility assessment, performance profiling and problem analysis and reliability consultation. Team Hitachi is ready to help you deliver a successful video device. The Hitachi CinemaStar product line is optimized for video applications, for any size system.

Specifications

| | |
|---|--|
| Model(s) | HCC542525K9SA00 HCC542516K9SA00 HCC542512K9SA00 HCC542580K9SA00 |
| Interface | Serial-ATA 1.5Gb/s |
| Capacity (GB) ¹ | 250 / 160 / 120 / 80 |
| Sector size (variable, Bytes/sector) | 512 |
| Recording zones | 24 |
| Data heads (physical) | 4 / 3 / 2 / 2 |
| Data Disks | 2 / 2 / 1 / 1 |
| Max. areal density (Gbits/sq. in.) | 205 |
| Performance | |
| Data buffer (MB) ² | 8 |
| Rotational speed (RPM) | 5400 |
| Latency average (ms) | 5.5 |
| Media transfer rate (Mbits/sec, max) | 665 |
| Interface transfer rate (MB/sec, max) | 150 |
| Seek time (read, typical) (avg. ms) | 13 |
| Reliability | |
| Load/unload | 600,000 |
| Availability ³ (hrs/day x days/wk) | 24x7 |
| Power | |
| Requirement | +5 VDC (+/-5%) |
| Startup (W, peak, max.) | 4.25 |
| Read / Write (W, avg.) | 1.8 |
| Physical size | |
| z-height (mm) | 9.5 |
| Dimensions (width x depth, mm) | 70 x 100 |
| Weight (g, typ.) | 102 / 95 |
| Environmental (operating) | |
| Operating temperature ⁴ | 5° to 65° C |
| Shock (half-sine wave) | 400 G (2ms), 200 G (1ms) |
| Environmental (non-operating) | |
| Ambient temperature | -40° to 65° C |
| Shock (half-sine wave) | 1000 G (1ms) |
| Acoustics (A-weighted sound power) | |
| Idle (Bels, typ.) | 2.4 |
| Op (Bels, typ.) | 2.6 |

¹ One GB is equal to one billion bytes when referring to hard drive capacity. Accessible capacity may be less.

² Upper 736KB of buffer capacity used for drive firmware

³ Low duty cycle, non mission-critical applications requiring up to 20 percent read/write activity per power-on-hour in digital video and consumer electronics applications. Customer environments may vary from application to application.

⁴ Temperature measured at base casting

Hitachi quality and service

Hitachi CinemaStar hard disk drives are designed to the highest quality standards and contain field-proven components. Hitachi provides worldwide technical support and integration services to enable global customers to bring their products to market quickly.

How to read the CinemaStar model number

HCC542525K9SA00 = 250 GB

H = Hitachi

C = CinemaStar

C = Compact

54 = 5400 RPM

25 = Full capacity — 250 GB

25 = Capacity this model, 25 = 250 GB
(16 = 160 GB, 12 = 120 GB, 80 = 80 GB)

K = Generation code

9 = 9.5mm z-height

SA = Serial ATA interface

0 = Reserved

0 = Reserved

Information and Technical Support

www.hitachigst.com (Main Web site)

www.hitachigst.com/partners (Partner Web site)

North America

support_usa@hitachigst.com

Toll free: 1 888 426-5214, Direct: 1 507 322-2370

Asia Pacific

support_ap@hitachigst.com / 65 6840 9595

EMEA and UK

support_uk@hitachigst.com / 44 20 7133 0032

Germany

support_uk@hitachigst.com / 49 6929 993601

Program Support

Partners First™ Program

channelpartners@hitachigst.com

Hitachi Global Storage Technologies' trademarks are authorized for use in countries and jurisdictions in which Hitachi Global Storage Technologies has the right to use, market and advertise the brands. Contact Hitachi Global Storage Technologies for further information. Hitachi Global Storage Technologies shall not be liable to third parties for unauthorized use of Hitachi Global Storage Technologies trademarks.

References in this publication to Hitachi Global Storage Technologies' products, programs, or services do not imply that Hitachi Global Storage Technologies intends to make these available in all countries in which it operates.

Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary. Please visit the Support section of our website, www.hitachigst.com/support, for additional information on product specifications. Photographs may show design models.

© 2007 Hitachi Global Storage Technologies

Hitachi Global Storage Technologies
3403 Yerba Buena Road
San Jose, CA 95135 USA

Produced in the United States 11/07.
All rights reserved.

Partners First™ and Smooth Stream™ are trademarks of Hitachi Global Storage Technologies.