

Quick installation guide Hitachi Microdrive CF+ Type II

Models: DSCM-11000
DSCM-10512
DSCM-10340



Handling precautions

- Follow these suggestions to optimize the use of your Hitachi Microdrive, as well as those devices in which it is installed:
- Do not seal the breather hole! Sealing the breather hole may result in loss of data.
- Do not press on the drive! Do not apply any force to the drive during handling or installation.
- Always handle the drive with care to prevent damage from shock, vibration, or electrostatic discharge (ESD).
- Handle the drive carefully by the edges. Do not touch any exposed printed circuit board.
- Do not write on the label or remove it. Do not apply additional labels.
- Always carry the drive in its plastic case.
- Do not drop the drive.
- Do not expose the drive to wet conditions.
- Do not place the drive near a strong magnetic field.
- Do not expose the drive to extreme temperatures.
- Do not use the drive in CF+™ Type II slots without an ejection mechanism.
- The Microdrive may become hot during operation. Be careful when removing the drive from the host device immediately after operation.

Quick installation procedure

Note: Back up all data before beginning installation!

Refer to the manual that came with your computer, camera, or other device to determine if it is compatible with the CF+ Type II or the PC card type II drive/interface adapter and to find instructions on inserting and removing the Hitachi Microdrive.

- *Using the Hitachi Microdrive with a PC card adapter*
With a PC card adapter the Hitachi Microdrive can be installed in devices such as digital cameras or PCs that have a PC card type II slot. If your Microdrive did not come with a PC card, it can be purchased separately.

With both facing upward (the arrow at the upper left corner of the Microdrive), slide the Hitachi Microdrive firmly along the track into the PC card adapter. [If either is not facing upward, the Microdrive will not fit into the track.]

Note: When inserting or removing the PC card, hold the PC card, not the Hitachi Microdrive.

- *Using the Hitachi Microdrive without a PC card adapter*

The Hitachi Microdrive is compatible with the CF+ Type II standard and can be used in devices with the CF+ Type II slot without a card adapter. Refer to the manual shipped with the device to determine its slot type.

If your PC does not recognize the Hitachi Microdrive

With the Plug & Play feature of Windows® 98 and 95 your PC should automatically recognize the Hitachi Microdrive. If it does not do so, do the following:

1. In Windows select *Start* and *Settings*.
2. Click *Control Panel*.
3. Click the *Hardware* icon, click *Next*.
4. Select *No* in the *Hardware Wizard*, click *Next*.
5. Select *Hard disk controller* as the hardware type, click *Next*.
6. Specify *Standard IDE/ESDI hard disk controller*

Operating systems

The Hitachi Microdrive has been tested for general compatibility with the following operating systems:

- Windows 98
- Windows 95
- Windows CE
- Apple® OS (refer to the URL below for the applicable operating systems)

Other operating systems may be compatible with the Hitachi Microdrive but have not been tested.

Product information

The latest product information can be obtained from

<http://www.hgst.com/products>

This includes

- technical tips
- complete product specifications
- a list of compatible devices

© Copyright Hitachi Global Storage Technologies

Hitachi Global Storage Technologies
5600 Cottle Road
San Jose, CA 95193

Produced in the United States

1/03

All rights reserved Deskstar™ is a trademark of Hitachi Global Storage Technologies.

Microsoft, Windows XP, and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other product names are trademarks or registered trademarks of their respective companies.

References in this publication to Hitachi Global Storage Technologies products, programs or services do not imply that Hitachi Global Storage Technologies intends to make these available in all countries in which Hitachi Global Storage Technologies operates.

Product information is provided for information purposes only and does not constitute a warranty.

Information is true as of the date of publication and is subject to change. Actual results may vary.

This publication is for general guidance only. Photographs may show design models.

13 January 2003
