




Ultrastar® Data60

Features

- Up to 60 Ultrastar® He12 HDDs (SAS or SATA)
- Hybrid support for up to 24 SSDs (SAS or SATA) to create a data acceleration tier
- Up to 720TB of raw storage in 4U
- Dual-port SAS for high availability or single-port SATA for low cost
- 4 rack units height, 712mm depth
- Up to 12 x 12Gb/s SAS3 host connections
- Patented IsoVibe technology ensures maximum performance even in heavy workloads
- Enterprise-grade redundant and hot-swappable PSUs, IO Modules and fans
- Improved cooling from innovative, patented ArcticFlow technology
- Rack-mounted top cover for quick and easy service
- 5-year limited warranty



60-Bay Hybrid Storage Platform

The Next Generation Hybrid Platform for Software-Defined Storage



Designed for High Density and Flexibility

The Ultrastar Data60 is a key element of next-generation disaggregated storage and software-defined storage (SDS) systems, delivering high density and the flexibility to balance performance with cost. The Ultrastar Data60 provides up to 720TB¹ of raw storage in a compact and efficient form factor. HGST HelioSeal® drives ensure cool running, quiet operation and high reliability. A high performance data tier can be set up for demanding applications by using SSDs in up to 24 of the drive slots, enabling the ability to serve both fast data and big data from a single platform.

Building on 50+ Years of Storage Design Experience

Conventional dense disk shelves frequently suffer from performance degradation due to induced vibration from adjacent drives. Traditional platforms also have cooling challenges as the cooling air passes over successive rows of drives, losing effectiveness as it gets heated up along the airflow path. Developing storage devices and platforms side-by-side, we address these challenges through vertical innovation, a set of technologies developed based on a holistic view of devices, platform, and their interactions. The first two of these patented technologies are IsoVibe™ and ArcticFlow™. IsoVibe reduces vibration-induced performance degradation, while ArcticFlow overcomes the cooling issues by introducing cool air into the middle of the platform. Both these technologies contribute to long-term reliability, enabling our five-year limited warranty on the entire platform.


Designed for the Enterprise and the Cloud

This new platform addresses the demanding storage needs of large enterprise customers, storage OEMs, cloud service providers and resellers/integrators that require dense, shared HDD or hybrid storage. The Ultrastar Data60 provides the flexibility to specify the HDD and SSD combinations to balance capacity, performance and cost.

¹One MB is equal to one million bytes, one GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes) when referring to storage capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the hard drives, the operating system and other factors.



Ultrastar® Data60



IsoVibe

IsoVibe Patented Vibration Isolation Technology

Precise cuts in the baseboard provide a suspension for the drives in the chassis, isolating them from transmitted vibration. The result is that consistent performance is maintained, even when all the drives are working hard.



ArcticFlow

ArcticFlow Patented Thermal Zone Cooling technology

By introducing cool air into the center of the chassis, drives operate at lower and more consistent temperatures than conventional systems. This results in lower fan speeds, reduced vibration, lower power consumption, quieter operation and ultimately higher reliability.

Specifications

Max. Drives	<ul style="list-style-type: none"> 60 x 3.5" drive bays Up to 24 can be SAS or SATA SSD
Drive Interface	<ul style="list-style-type: none"> 12Gb/s SAS 6Gb/s SATA
Available Drive Capacities	<ul style="list-style-type: none"> HDD up to 12TB SSD up to 6.4TB
Host Interface	<ul style="list-style-type: none"> Dual redundant I/O Modules (IOM), 6 Mini-SAS HD ports per IOM
Weight	<ul style="list-style-type: none"> 4U60 w/o drives: 27.3kg (60lbs) 4U60 w/ 60 HDDs: 79.4kg (175lbs)
LED Indicators	<ul style="list-style-type: none"> Front/Rear: Power, ID, Fault Drive: Activity, Fault
Physical Dimensions	<ul style="list-style-type: none"> Height: 175mm (6.89") Width: 447mm (17.61") Depth: 712mm (28.03") Depth in Rack: Max of 890mm (35.04") w/ dual CMA—includes 24 SAS cables
Management	<ul style="list-style-type: none"> SCSI Enclosure Services Redfish (out of band, via RJ45)
Power	<ul style="list-style-type: none"> Dual 1600W, 80+ Platinum 200-240V AC input, auto ranging, 50-60Hz
Cooling	<ul style="list-style-type: none"> 4 main enclosure fans, front-to-rear system cooling with zero-loss backflow prevention 1 IO module fan Dual PSUs with built-in fans
Environmental	<ul style="list-style-type: none"> Operating Temperature: 5 to 40°C Non-op Temperature: -40 to 60°C Humidity: 5 to 85% relative humidity Operating Altitude: 40°C @ 3,000ft Sound Power: < 7.2 Bels @ 23±2°C
Serviceability	<ul style="list-style-type: none"> Cable-free hot-swappable IOM, power supply, fans and drives

Contact

Sales Inquiries
 North America: salesNA@hgst.com
 Europe/Middle East/Africa (EMEA): salesEMEA@hgst.com
 Asia/Pacific: salesAP@hgst.com
 Japan: salesJP@hgst.com

Information & Technical Support
<http://www.hgst.com/support/platforms-support>

Partner Program Inquiries
channelpartners@hgst.com

Western Digital Corporation
 5601 Great Oaks Parkway
 San Jose, CA 95119 USA

© 2018 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the HGST logo, ArcticFlow, HelioSeal, IsoVibe, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. All other marks are the property of their respective owners.